

3M Scotchkote™ FP 812 External Wall Coating

Category : Other Engineering Material

Material Notes:

3M Scotchkote External Wall Coating FP 812 has been specifically developed as a low maintenance, high build coating for cementitious and plaster wall surfaces. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotchkote-FP-812-External-Wall-Coating.php

| Physical Properties | Metric | English | Comments |
|--|-------------|---------------------------|----------|
| Density | 1.35 g/cc | 0.0488 lb/in ³ | |
| Solids Content | 60 % | 60 % | |
| Volatile Organic Compounds (VOC) Content | 0.00 g/l | 0.00 g/l | |
| Thickness | 229 microns | 9.00 mil | DFT |
| | 406 microns | 16.0 mil | WFT |

| Processing Properties | Metric | English | Comments |
|-----------------------|----------|------------|-----------|
| Cure Time | 30.0 min | 0.500 hour | Touch Dry |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| Appearance | White | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China