

3M Scotchkote™ LW 405 Epoxy Concrete Mortar

Category : Polymer , Thermoset , Polyurethane, TS , Thermoset Polyurethane, Liquid

Material Notes:

Scotchkote Epoxy Concrete Mortar LW 405 has been specifically developed as a three component 100% solids light weight repair mortar for use on concrete surfaces. Product Features: Designed for application by trowel or float Can be used to form wall/floor coverings Excellent hold up on vertical and overhead surfaces High abrasion resistance and excellent adhesion Unaffected by most industrial chemicals Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotchkote-LW-405-Epoxy-Concrete-Mortar.php

Physical Properties	Metric	English	Comments
Solids Content	100 %	100 %	
Volatile Organic Compounds (VOC) Content	0.00 g/l	0.00 g/l	
pH	10	10	
Thickness	5990 microns	236 mil	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	80	80	
Compressive Strength	41.4 MPa	6000 psi	ASTM D695

Processing Properties	Metric	English	Comments
Cure Time	480 min	8.00 hour	Hard Dry
	1440 min	24.0 hour	Full Hardness
	10100 min	168 hour	Full Cure

Descriptive Properties	Value	Comments
Appearance	Light Gray	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China