

3M Scotchkote™ SP 810 Epoxy Sealer

Category : Polymer , Thermoset , Epoxy

Material Notes:

Scotchkote Epoxy Sealer SP 810 has been specifically developed as a low viscosity primer/sealer for concrete and cementitious surfaces prior to application of other Scotchkote 100% solids epoxy system. Product Features: Combines good application characteristics with excellent penetration and adhesion. Designed for application by brush or roller. Designed for use on concrete surfaces but can be used on other porous mineral substrates. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotchkote-SP-810-Epoxy-Sealer.php

Physical Properties	Metric	English	Comments
Density	1.10 g/cc	0.0397 lb/in ³	
Solids Content	100 %	100 %	
Thickness	102 microns	4.00 mil	

Processing Properties	Metric	English	Comments
Cure Time	120 min	2.00 hour	Touch Dry
	960 min	16.0 hour	Hard Dry
	10100 min	168 hour	Full Cure

Descriptive Properties	Value	Comments
Appearance	Clear	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China