

3M XR4123 Double Coated Film Tape

Category : Polymer , Adhesive

Material Notes:

3M™ X-Series Industrial Attachment Tapes offer a variety of performance characteristics and product constructions to support demanding application requirements. This product line provides a range of adhesive transfer and double-coated tapes designed for attachment of paper, corrugated, films, foils, fabric, plastics and metal. Double Coated (DC) tapes provide a backing for improved handling. Adhesive Transfer Tapes (ATT) provide the thinnest bond lines. The 3M™ X-Series Tape System is manufactured in the United States by 3M

Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-XR4123-Double-Coated-Film-Tape.php

Physical Properties	Metric	English	Comments
Thickness	76.2 microns	3.00 mil	Release Liner
	229 microns	9.00 mil	Tape

Mechanical Properties	Metric	English	Comments
Peel Strength	1.0628 kN/m	6.0625 pli	Stainless Steel, Faceside, 180° Peel, 2 mil Al
	1.118 kN/m	6.375 pli	Stainless Steel, Backside, 180° Peel, 2 mil Al

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	49.0 °C	120 °F	Short Term
	66.0 °C	151 °F	Long Term

Processing Properties	Metric	English	Comments
Shelf Life	18.0 Month	18.0 Month	

Descriptive Properties	Value	Comments
Adhesive Carrier	High Density Polyethylene	
Adhesive Type	Synthetic Rubber	
Liner	White Densified Kraft Liner with Red Print	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China