

A. Schulman POLYBATCH™ FTA-50-P Concentrate Based In LLDPE

Category: Other Engineering Material, Additive/Filler for Polymer, Polymer, Thermoplastic, Polyethylene (PE), LLDPE

Material Notes:

DescriptionPOLYBATCH® FTA-50-P is the next generation antiblock masterbatch to POLYBATCH® F-50-AP (50% DE in LLDPE). This masterbatch contains 50% film grade talc based in LLDPE. POLYBATCH® FTA-50P offers better COF development, equal or better clarity, and excellent antiblocking performance over products produced with a comparable loading of DE. POLYBATCH® FTA-50P is recommended for use in polyethylene blown and cast film applications where high antiblock levels are required. POLYBATCH® FTA-50P is typically recommended for use at a 1 to 2% loading level.Information provided by A. Schulman.

Order this product through the following link:

http://www.lookpolymers.com/polymer_A-Schulman-POLYBATCH-FTA-50-P-Concentrate-Based-In-LLDPE.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.30 g/cc	1.30 g/cc	ASTM D792
Melt Flow	9.0 g/10 min	9.0 g/10 min	ASTM D1238
	@Load 2.16 kg, Temperature 190 °C	@Load 4.76 lb, Temperature 374 °F	
Ash	50 %	50 %	

Descriptive Properties	Value	Comments
Moisture (max)	1000	ppm, ASTM D789
Pellet Count	70	pellets/gram

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China