

A. Schulman POLYTROPE™ TPP 508 Injection Molding Grade Olefinic Thermoplastic Elastomer

Category : Polymer , Thermoplastic , Elastomer, TPE , Olefinic TPE , Thermoplastic Olefinic Elastomer (TPO)

Material Notes:

Description Polytrope TPP 508 is an injection molding grade olefinic thermoplastic elastomer. This product has excellent low temperature impact properties and flow characteristics suitable for molding large automotive parts, such as fascias and air dams. TPP 508 is UV stable, paintable and pigmentable. Information provided by A. Schulman.

Order this product through the following link:

http://www.lookpolymers.com/polymer_A-Schulman-POLYTROPE-TPP-508-Injection-Molding-Grade-Olefinic-Thermoplastic-Elastomer.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.910 g/cc	0.910 g/cc	ASTM D792
Linear Mold Shrinkage	0.011 - 0.013 cm/cm	0.011 - 0.013 in/in	
Melt Index of Compound	10 g/10 min	10 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	60	60	ASTM D2240
Tensile Strength at Break	17.2 MPa	2500 psi	ASTM D638
Elongation at Break	600 %	600 %	ASTM D638
Flexural Modulus	0.552 GPa	80.0 ksi	ASTM D790
Gardner Impact	36.0 J @Temperature -30.0 °C	26.6 ft-lb @Temperature -22.0 °F	

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-50.0 °C	-58.0 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China