

A. Schulman PP 1227E-01 Polypropylene High-Impact Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene, Film Grade

Material Notes:

Description Polypropylene PP 1277E-01 is a low-flow, high-impact polypropylene for film, profile, tubing and coating. Information provided by A. Schulman.

Order this product through the following link:

http://www.lookpolymers.com/polymer_A-Schulman-PP-1227E-01-Polypropylene-High-Impact-Polypropylene.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.900 g/cc	0.900 g/cc	ASTM D792
Melt Flow	0.80 g/10 min @Load 2.16 kg, Temperature 230 °C	0.80 g/10 min @Load 4.76 lb, Temperature 446 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	80	80	ASTM D785
Tensile Strength at Break	20.7 MPa	3000 psi	at max load; ASTM D638
Elongation at Yield	10 %	10 %	ASTM D638
Flexural Modulus	1.00 GPa	145 ksi	ASTM D790
Izod Impact, Notched	NB	NB	ASTM D256
Izod Impact, Unnotched	NB	NB	ASTM D256
Gardner Impact	33.9 J	25.0 ft-lb	ASTM D5420

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	76.0 °C	169 °F	ASTM D648
Deflection Temperature at 1.8 MPa (264 psi)	50.0 °C	122 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China