

## A. Schulman PP 2268-01 Polypropylene High Flow, Impact Copolymer Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene Copolymer

### Material Notes:

Description Polypropylene PP 2268-01 is an automotive recognized high flow impact copolymer polypropylene. Application PP 2173-01 is intended for use in interior trim applications. Information provided by A. Schulman.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_A-Schulman-PP-2268-01-Polypropylene-High-Flow-Impact-Copolymer-Polypropylene.php](http://www.lookpolymers.com/polymer_A-Schulman-PP-2268-01-Polypropylene-High-Flow-Impact-Copolymer-Polypropylene.php)

Physical Properties	Metric	English	Comments
Specific Gravity	0.900 g/cc	0.900 g/cc	ASTM D792
Melt Flow	35 g/10 min	35 g/10 min	ASTM D1238
	@Load 2.16 kg, Temperature 230 °C	@Load 4.76 lb, Temperature 446 °F	

Mechanical Properties	Metric	English	Comments
Flexural Modulus	1.17 GPa	170 ksi	ASTM D790
Izod Impact, Notched	0.801 J/cm	1.50 ft-lb/in	ASTM D256
Gardner Impact	19.0 J	14.0 ft-lb	ASTM D3029
	6.78 J	5.00 ft-lb	ASTM D3029
	@Temperature -29.0 °C	@Temperature -20.2 °F	

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	93.3 °C	200 °F	ASTM D648

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China