

AIM CASTIN Solder for Photonic Packaging

Category : Metal , Nonferrous Metal , Solder/Braze Alloy

Material Notes:

Uses include:Fiber to Ferrule SolderingLaser Die AttachHermetic Packaging & SealingWetting & Sealing Laser OpticsThermal ManagementInformation provided by AIM Specialty Materials.

Order this product through the following link:

http://www.lookpolymers.com/polymer_AIM-CASTIN-Solder-for-Photonic-Packaging.php

Physical Properties	Metric	English	Comments
Density	7.30 g/cc	0.264 lb/in ³	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	276 MPa	40000 psi	

Thermal Properties	Metric	English	Comments
CTE, linear	40.0 $\mu\text{m}/\text{m}\cdot\text{°C}$	22.2 $\mu\text{in}/\text{in}\cdot\text{°F}$	
	@Temperature 20.0 °C	@Temperature 68.0 °F	
Melting Point	217 °C	423 °F	
Solidus	217 °C	423 °F	
Liquidus	217 °C	423 °F	

Descriptive Properties	Value	Comments
Creep Resistance	High	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China