

## **Abatron AboCrete Cement/Grout Resurfacing and Patching Epoxy**

Category: Polymer, Thermoset, Epoxy

## **Material Notes:**

Cement/grout resurfacing and patching epoxy for industrial, marine, institutional, and residential uses. The ultimate restoration and resurfacing material structurally and chemically superior to concrete. Welds permanently to concrete, metal, wood, and most surfaces. AboCrete provides structural and decorative patching, resurfacing and restoration. It fills cracks and replaces missing sections of concrete, marble, granite, and other stones. It bonds broken sections together, anchors posts and railings. Hardens in approximately 1 to 6 hours depending on the temperature, thickness, amount of aggregate and other variables. It can be applied with simple hand tools or by brush, paint roller, or squeegee. Information provided by Abatron.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Abatron-AboCrete-CementGrout-Resurfacing-and-Patching-Epoxy.php

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	62.1 MPa	9000 psi	Compared to 300 for concrete
Flexural Strength	72.4 MPa	10500 psi	Compared to 500 for concrete
Compressive Strength	82.7 MPa	12000 psi	Compared to 3500 for concrete

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China