

Abatron AboWeld 8104-13 Polysulfide-Epoxy Sealant and Caulk

Category: Polymer, Adhesive, Thermoset, Epoxy, Epoxy Adhesive

Material Notes:

AboWeld 8104-13 is a 2-part, 100% solids, liquid or filled polysulfide-epoxy. It is available in many colors. It has high hardness and rigidity, very low elongation, and is often used with sand or other fillers and pigments for patching, bonding, filling holes, etc. It is mainly used as a resurfacing coating, adhesive, and filler.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Abatron-AboWeld-8104-13-Polysulfide-Epoxy-Sealant-and-Caulk.php

Physical Properties	Metric	English	Comments
Solids Content	100 %	100 %	

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	70	70	
Tensile Strength at Break	19.0 MPa	2750 psi	
Elongation at Break	25 - 30 %	25 - 30 %	

Processing Properties	Metric	English	Comments
Cure Time	1440 - 4320 min	24.0 - 72.0 hour	(1-3 Days)
Pot Life	20 min	20 min	

Descriptive Properties	Value	Comments
Color	Many Colors	
Parts by Weight (pbw)	1	Part A
	1	Part B

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China