

Adamas Adalon® 812 PTFE, 46% Bronze, Green

Category : Polymer , Thermoplastic , Fluoropolymer , PTFE , Polytetrafluoroethylene (PTFE), Bronze Filled

Material Notes:

Information provided by Adamas, HPM

Order this product through the following link:

http://www.lookpolymers.com/polymer_Adamas-Adalon-812-PTFE-46-Bronze-Green.php

Physical Properties	Metric	English	Comments
Specific Gravity	3.28 - 3.31 g/cc	3.28 - 3.31 g/cc	ASTM D792
Deformation	7.0 - 10 %	7.0 - 10 %	ASTM D621

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	56 - 58	56 - 58	ASTM D2240
Ball Indentation Hardness	46.0 - 50.0 MPa	6670 - 7250 psi	ISO 2032-N132
Tensile Strength at Break	>= 20.0 MPa	>= 2900 psi	ASTM D4745-11
Elongation at Break	>= 220 %	>= 220 %	ASTM D4745-11
Coefficient of Friction, Dynamic	0.13 - 0.15	0.13 - 0.15	ASTM D1894
Coefficient of Friction, Static	0.15 - 0.16	0.15 - 0.16	ASTM D1894

Thermal Properties	Metric	English	Comments
Melting Point	327 °C	621 °F	DSC
Maximum Service Temperature, Air	260 °C	500 °F	DSC
Minimum Service Temperature, Air	-100 °C	-148 °F	DSC
Flammability, UL94	V-0	V-0	

Electrical Properties	Metric	English	Comments
Volume Resistivity	1.00e+7 ohm-cm	1.00e+7 ohm-cm	ASTM D257

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China