

## Addcomp ADD-VANCE® DS 785 Desiccant masterbatch in PP carrier

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoplastic , Polypropylene (PP)

### Material Notes:

Fields of application: Highly concentrated desiccant masterbatch for HDPE and PP.Examples: Elimination of moisture from (recycle) polymers in moisture sensitive applications.Mode of action and advantages: ADD-VANCE®DS 785 is a ready-for-use highly concentrated desiccant masterbatch. It contains additives that chemically bond moisture. ADD-VANCE®DS 785 has been designed for use with recycling materials as well as for applications sensitive to the effects of moisture.Advantages: Reduction or elimination of moisture in recycled polymers, thus allowing increased addition levels of recycle polymers; Reduction or prevention of lacing and windows/lenses in films, surface defects in moulding, porosity and die build-up; Non-sticking pellets, dust free dosing; and Safe and easy handling.Information provided by ADDCOMP

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Addcomp-ADD-VANCE-DS-785-Desiccant-masterbatch-in-PP-carrier.php](http://www.lookpolymers.com/polymer_Addcomp-ADD-VANCE-DS-785-Desiccant-masterbatch-in-PP-carrier.php)

| Physical Properties | Metric             | English                            | Comments |
|---------------------|--------------------|------------------------------------|----------|
| Bulk Density        | 0.650 - 0.800 g/cc | 0.0235 - 0.0289 lb/in <sup>3</sup> |          |

| Processing Properties  | Metric    | English   | Comments |
|------------------------|-----------|-----------|----------|
| Processing Temperature | <= 300 °C | <= 572 °F |          |

| Descriptive Properties | Value                       | Comments                   |
|------------------------|-----------------------------|----------------------------|
| Appearance             | White to off-white granules |                            |
| Dosing Level           | 0.5-2%                      | Film extrusion and molding |
|                        | 1-3%                        | Compounding                |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China