

American Computer Optics 18in Tempered LCD Glass

Category: Ceramic, Glass, Filter, Optical

Material Notes:

Maximum Size: 12.15" X 15.28"Abrasion: MIL-C-675C, section 4.5.11Adhesion: MIL-C-48497A, para 4.5.3.1Humidity: The coated optical surface will show no signs of deterioration after a 24 hour humidity exposure (50 C, 95% humidity)Solubility: The coated optical surface will show no signs of deterioration after a 24 hour immersion or exposure at room temperature (-60 F to + 90F) in each of the following solutions: Distilled Water - Acetone - Ethyl Alcohol - Isopropyl Alcohol - Trichloroethylene - 1.1.1 TrichlorethaneTempering: ATSM C1048-976Information provided by American Computer Optics.

Order this product through the following link:

http://www.lookpolymers.com/polymer_American-Computer-Optics-18in-Tempered-LCD-Glass.php

Physical Properties	Metric	English	Comments
Thickness	3000 microns	118 mil	

Optical Properties	Metric	English	Comments
Transmission, Visible	98 %	98 %	
IR Transmittance	70 %	70 %	
	@Wavelength 780 - 2500 nm	@Wavelength 780 - 2500 nm	Near IR
UV Transmittance	47 %	47 %	
	@Wavelength 300 - 380 nm	@Wavelength 300 - 380 nm	
Reflection Coefficient, Visible (0-1)	<= 0.010	<= 0.010	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China