

Aremco Ceramabind™ 642 High Temperature Inorganic Binder

Category : Ceramic

Material Notes:

A basic solution which is highly compatible with most ceramic and metal powders. Good wettability and tack, and excellent acid resistance after curing. Extremely moisture resistant after a high temperature cure. Sets up in thick cross-sections when properly formulated.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Aremco-Ceramabind-642-High-Temperature-Inorganic-Binder.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.41 g/cc	1.41 g/cc	
Solids Content	40 %	40 %	by weight
pH	10.7	10.7	
Viscosity	370 cP	370 cP	
Storage Temperature	7.22 - 35.0 °C	45.0 - 95.0 °F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1650 °C	3000 °F	

Processing Properties	Metric	English	Comments
Shelf Life	6.00 Month	6.00 Month	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China