

Aremco Ceramabind™ 644-A High Temperature Inorganic Binder

Category : Ceramic

Material Notes:

An acidic, colloidal alumina binder developed for mixing with sized refractory flours and grains to produce high temperature refractory coatings for ceramic fiber boards. Used as a superior standalone system to rigidize refractory fiber shapes.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Aremco-Ceramabind-644-A-High-Temperature-Inorganic-Binder.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.23 g/cc	1.23 g/cc	
Solids Content	30 %	30 %	by weight
pH	4.0	4.0	
Viscosity	7.0 cP	7.0 cP	
Storage Temperature	7.22 - 35.0 °C	45.0 - 95.0 °F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1650 °C	3000 °F	

Processing Properties	Metric	English	Comments
Shelf Life	6.00 Month	6.00 Month	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China