

## Aremco Pyro-Putty™ 1500 High Temperature Ceramic-Metallic Putty, Ceramic Filled

Category : Ceramic , High Temp Ceramic Resin

**Material Notes:**

Ceramic-Filled, One-Part, Thixotropic Based Paste. Used Primarily to Seal Boiler Doors and Molten Metal Systems. Easy to Apply and Removable; For uses to 2300°F

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Aremco-Pyro-Putty-1500-High-Temperature-Ceramic-Metallic-Putty-Ceramic-Filled.php](http://www.lookpolymers.com/polymer_Aremco-Pyro-Putty-1500-High-Temperature-Ceramic-Metallic-Putty-Ceramic-Filled.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.27 g/cc	1.27 g/cc	
Storage Temperature	4.44 - 32.2 °C	40.0 - 90.0 °F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1260 °C	2300 °F	

Processing Properties	Metric	English	Comments
Cure Time	60.0 min	1.00 hour	1-2 hrs Air Set; 1 hr at 200°F
Shelf Life	6.00 Month	6.00 Month	

Descriptive Properties	Value	Comments
Color	Gray Brwon	
Filler	Ceramic Fiber	

### Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China