

## Aremco Pyro-Putty™ 2400 High Temperature Ceramic-Metallic Putty, Stainless Filled

Category : Ceramic , High Temp Ceramic Resin

**Material Notes:**

Ceramic and Stainless-Filled, One-Part, Water Based Paste. For Applications to 3/8" Thick. Repairs Cast Iron, Steel and Stainless Parts to 2000°F

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Aremco-Pyro-Putty-2400-High-Temperature-Ceramic-Metallic-Putty-Stainless-Filled.php](http://www.lookpolymers.com/polymer_Aremco-Pyro-Putty-2400-High-Temperature-Ceramic-Metallic-Putty-Stainless-Filled.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.50 g/cc	1.50 g/cc	
Storage Temperature	4.44 - 32.2 °C	40.0 - 90.0 °F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1090 °C	2000 °F	

Processing Properties	Metric	English	Comments
Cure Time	120 - 240 min	2.00 - 4.00 hour	2-4 hrs Air Set; 2-4 hrs at 200°F
Shelf Life	6.00 Month	6.00 Month	

Descriptive Properties	Value	Comments
Color	Metallic Gray	
Filler	Stainless	

### Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China