

Aremco Pyro-Putty™ 2500 High Temperature Ceramic-Metallic Putty, Iron Oxide Filled

Category : Ceramic , High Temp Ceramic Resin

Material Notes:

Ceramic and Black Iron Oxide-Filled, One-Part, Water Based Paste.For Applications to 1/4" Thick.Repairs Cast Iron, and Steel Parts to 1600°F

Order this product through the following link:

http://www.lookpolymers.com/polymer_Aremco-Pyro-Putty-2500-High-Temperature-Ceramic-Metallic-Putty-Iron-Oxide-Filled.php

Physical Properties	Metric	English	Comments
Specific Gravity	2.90 g/cc	2.90 g/cc	
Storage Temperature	4.44 - 32.2 °C	40.0 - 90.0 °F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	871 °C	1600 °F	

Processing Properties	Metric	English	Comments
Cure Time	300 - 420 min	5.00 - 7.00 hour	2-4 hrs Air Set; 3 hrs at 200°F
Shelf Life	6.00 Month	6.00 Month	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China