

Aremco Pyro-Putty™ 653 High Temperature Ceramic-Metallic Putty, Stainless Filled

Category : Ceramic , High Temp Ceramic Resin

Material Notes:

Ceramic and Stainless-Filled, One-Part, Water Based Paste. For Vertical Surfaces and Applications to 1/2" Thick. Repairs Cast Iron, Steel and Stainless Parts to 2000°F.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Aremco-Pyro-Putty-653-High-Temperature-Ceramic-Metallic-Putty-Stainless-Filled.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.90 g/cc	1.90 g/cc	
Storage Temperature	4.44 - 32.2 °C	40.0 - 90.0 °F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1090 °C	2000 °F	

Processing Properties	Metric	English	Comments
Cure Time	180 - 240 min	3.00 - 4.00 hour	2-4 hrs Air Set; 3 hrs at 200°F
Shelf Life	6.00 Month	6.00 Month	

Descriptive Properties	Value	Comments
Color	Metallic Gray	
Filler	Stainless	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China