

## Aremco Pyro-Putty™ 950 High Temperature Ceramic-Metallic Putty, Ceramic Fiber Filled

Category : Ceramic , High Temp Ceramic Resin

**Material Notes:**

Ceramic Fiber-Filled, Organic Caulk.For Sealing High Temperature Joints to 950°F.Cures Into a Tough, Pliable, Inert Material.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Aremco-Pyro-Putty-950-High-Temperature-Ceramic-Metallic-Putty-Ceramic-Fiber-Filled.php](http://www.lookpolymers.com/polymer_Aremco-Pyro-Putty-950-High-Temperature-Ceramic-Metallic-Putty-Ceramic-Fiber-Filled.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.09 g/cc	1.09 g/cc	
Storage Temperature	4.44 - 32.2 °C	40.0 - 90.0 °F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	510 °C	950 °F	

Processing Properties	Metric	English	Comments
Cure Time	60.0 min	1.00 hour	
	@Temperature 204 °C	@Temperature 400 °F	
Shelf Life	360 min	6.00 hour	
	@Temperature 107 °C	@Temperature 225 °F	
Shelf Life	6.00 Month	6.00 Month	

Descriptive Properties	Value	Comments
Color	Silver Gray	
Filler	Ceramic Fiber	

### Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China