

## Arkema Group Lacovyl® PB 1302 H PVC

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Foam Grade

### Material Notes:

LACOVYL PB 1302 H is a vinyl chloride homopolymer manufactured by micro-suspension polymerization process for the preparation of plastisols. It is specially designed for compact articles with low plasticizer content. \* MAIN CHARACTERISTICS Viscosity index (ISO 1628-2): 125 ml/g, (K value: 70). \* APPLICATIONS LACOVYL PB 1302 H is recommended for the following applications : high gloss and crystal clear surface coats, impregnation layer for floor coverings, compact coatings for wall covering and coated fabrics, foam layer for artificial leather, coating by mechanical foam techniques, rotomolding (toys, automotive industry, etc), dip molding, compact or foamed cap closures. ISO data provided by the manufacturer, Arkema.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Arkema-Group-Lacovyl-PB-1302-H-PVC.php](http://www.lookpolymers.com/polymer_Arkema-Group-Lacovyl-PB-1302-H-PVC.php)

| Physical Properties | Metric                 | English                | Comments         |
|---------------------|------------------------|------------------------|------------------|
| Viscosity Test      | 127 cm <sup>3</sup> /g | 127 cm <sup>3</sup> /g | Viscosity Number |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China