

## Arkema Group Lacovyl® PB 1302 PVC

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Molded

### Material Notes:

LACOVYL PB 1302 is a vinyl chloride homopolymer manufactured by microsuspension polymerization process for the preparation of plastisols. It is specially designed for compact articles with low plasticizer content. \* MAIN CHARACTERISTICS Viscosity index (ISO 1628-2): 125 ml/g, (K value: 70). \* APPLICATIONS LACOVYL PB 1302 is recommended for the following applications: high gloss and crystal clear surface coats, impregnation layer for the floor coverings, compact coatings for wall covering and coated fabrics, coating by mechanical foam techniques, rotomolding (toys, automotive industry, etc...), - dip molding. ISO data provided by the manufacturer, Arkema.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Arkema-Group-Lacovyl-PB-1302-PVC.php](http://www.lookpolymers.com/polymer_Arkema-Group-Lacovyl-PB-1302-PVC.php)

Physical Properties	Metric	English	Comments
Viscosity Test	125 cm <sup>3</sup> /g	125 cm <sup>3</sup> /g	Viscosity Number

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China