

Arkema Group Lacovyl® S 071 S PVC

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Molded

Material Notes:

LACOVYL S 071 S is a low molecular weight vinyl chloride homopolymer produced by a suspension polymerization process. Characteristics : - Viscosity index (ISO 1628-2):79 ml/g,(K value:57). Apparent density (ISO 60):0.58 g/ml. good low temperature fusion characteristics. suitable for dry blend preparation providing a controlled feed to production machines. excellent base color and thermal stability. Provides finished products with good transparency and free from fish eyes.* RECOMMENDED APPLICATIONS Bottles by extrusion and injection blow molding. LACOVYL is also recommended for biaxial orientation processes. Calendering of rigid sheet. Extrusion of rigid film and sheet. * EXAMPLES OF APPLICATIONSPVC-U: NAKAN RMA 705 N NAKAN RMS 501 L ISO data provided by the manufacturer, Arkema.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Arkema-Group-Lacovyl-S-071-S-PVC.php

Physical Properties	Metric	English	Comments
Viscosity Test	79 cm ³ /g	79 cm ³ /g	Viscosity Number

Optical Properties	Metric	English	Comments
Transmission, Visible	80 %	80 %	Mfr. reports 'Transparent' but doesn't quantify.

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China