

Arkema Group OREVAC® 18360 Maleic Anhydride Modified Polyethylene

Category : Polymer , Thermoplastic , Polyethylene (PE) , Anhydride-Modified Polyethylene

Material Notes:

OREVAC® 18360 is anhydride modified polyethylene. It is available in pellet form for use in conventional extrusion and coextrusion equipment designed to process polyethylene (PE) resins. OREVAC® 18360 provides outstanding adhesion to PE, EVOH and PA. It is typically used as tie-layer in multilayer structures. It is mainly used in flexible packaging for the production of multilayer barrier films. Information provided by Arkema Group

Order this product through the following link:

http://www.lookpolymers.com/polymer_Arkema-Group-OREVAC-18360-Maleic-Anhydride-Modified-Polyethylene.php

Physical Properties	Metric	English	Comments
Density	0.914 g/cc @Temperature 23.0 °C	0.0330 lb/in ³ @Temperature 73.4 °F	ISO 1183
Melt Index of Compound	2.0 g/10 min @Load 2.16 kg, Temperature 190 °C	2.0 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Thermal Properties	Metric	English	Comments
Melting Point	120 °C	248 °F	DSC
Vicat Softening Point	87.0 °C	189 °F	ISO 306

Processing Properties	Metric	English	Comments
Adapter Temperature	230 °C	446 °F	
Head Temperature	230 °C	446 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China