

Arkema Group OREVAC® 18921A Epoxide Modified Polyethylene

Category : Polymer , Thermoplastic , Polyethylene (PE)

Material Notes:

OREVAC® 18921A is epoxide modified polyethylene. It is available in pellet form for use in conventional extrusion and coextrusion equipment designed to process polyethylene (PE) resins. OREVAC® 18921A provides outstanding adhesion to Polyethylene and Polyester. It is typically used to bond PET and PE in transparent thermoformed containers. Information provided by Arkema Group

Order this product through the following link:

http://www.lookpolymers.com/polymer_Arkema-Group-OREVAC-18921A-Epoxide-Modified-Polyethylene.php

| Physical Properties | Metric | English | Comments |
|------------------------|--|--|----------|
| Density | 0.910 g/cc @Temperature 23.0 °C | 0.0329 lb/in ³ @Temperature 73.4 °F | ISO 1183 |
| Melt Index of Compound | 7.0 g/10 min @Load 2.16 kg, Temperature 190 °C | 7.0 g/10 min @Load 4.76 lb, Temperature 374 °F | ISO 1133 |

| Thermal Properties | Metric | English | Comments |
|-----------------------|---------|---------|----------|
| Melting Point | 106 °C | 223 °F | DSC |
| Vicat Softening Point | 75.0 °C | 167 °F | ISO 306 |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China