

Arkema Group Orevac® 18216 Maleic Anhydride modified EVA

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate

Material Notes:

Orevac® 18216 resin is a maleic anhydride modified ethylene - vinyl acetate copolymer designed for the coextrusion of multilayer barrier structures providing outstanding adhesion between layers. Information provided by Arkema Group

Order this product through the following link:

http://www.lookpolymers.com/polymer_Arkema-Group-Orevac-18216-Maleic-Anhydride-modified-EVA.php

Physical Properties	Metric	English	Comments
Density	0.970 g/cc	0.0350 lb/in ³	ASTM D1505
Melt Flow	2.0 g/10 min @Load 2.16 kg, Temperature 190 °C	2.0 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238

Thermal Properties	Metric	English	Comments
Melting Point	80.0 °C	176 °F	D.S.C. method
Vicat Softening Point	50.0 °C	122 °F	ASTM D1525-82

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China