

## Arlon 15370T020 0.020" (0.508 mm) Uncatalyzed, Unsupported Rubber on a Mylar Carrier

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

**Material Notes:**

Design/Construction:Side 1: Uncatalyzed, Unsupported Rubber on a Mylar CarrierAppearance: Translucent high viscosity gumThis data represents typical values for the production material. The data should not be used to write, or in place of, material specifications.Information provided by Arlon, Silicone Technologies Division

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Arlon-15370T020-0020-0508-mm-Uncatalyzed-Unsupported-Rubber-on-a-Mylar-Carrier.php](http://www.lookpolymers.com/polymer_Arlon-15370T020-0020-0508-mm-Uncatalyzed-Unsupported-Rubber-on-a-Mylar-Carrier.php)

Physical Properties	Metric	English	Comments
Thickness	38.1 microns	1.50 mil	Mylar Carrier
	76.2 microns	3.00 mil	Poly Interleave
	457 - 559 microns	18.0 - 22.0 mil	Overall
	457 - 559 microns	18.0 - 22.0 mil	Side 1

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	232 °C	450 °F	
Minimum Service Temperature, Air	-56.7 °C	-70.0 °F	

Processing Properties	Metric	English	Comments
Shelf Life	6.00 Month	6.00 Month	From date of manufacture
	@Temperature 23.9 °C	@Temperature 75.0 °F	

Descriptive Properties	Value	Comments
Color	Blue	Interleave
	Naturally Translucent	
Total Product Weight (oz/yd2)	19	Compound Property

### Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China