

## **Axiall 12881 Wire & Cable Flexible PVC**

Category: Polymer, Thermoplastic, Vinyl (PVC), PVC, Wire and Cable Grade

## **Material Notes:**

Flame retardant, specialty grade, 75°C rated jacket compound. Designed to present a unique clear, sparkling appearance to the finished cable. Information provided by Georgia GulfGeorgia Gulf became Axiall Corporation in 2013.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Axiall-12881-Wire-Cable-Flexible-PVC.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.30 - 1.34 g/cc	1.30 - 1.34 g/cc	ASTM D-792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	85 - 91	85 - 91	delayed; ASTM D-2240
Tensile Strength, Yield	19.3 MPa	2800 psi	ASTM D-638
Elongation at Yield	290 %	290 %	ASTM D-638
100% Modulus	0.0134 GPa	1.95 ksi	ASTM D-638

Thermal Properties	Metric	English	Comments
Oxygen Index	29 %	29 %	ASTM D-638

Processing Properties	Metric	English	Comments
Melt Temperature	182 °C	360 °F	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China