

Axiall MD-5009 Rigid PVC, Molding

Category : Polymer , Thermoplastic , Vinyl (PVC)

Material Notes:

Georgia Gulf MD-5009 is a rigid, fitting-grade PVC compound designed for hot spruce/runner molds, large parts and multi-cavity molds.

This compound is characterized by excellent processability, which includes color hold, regrind stability and surface appearance. MD-5009

is NSF listed under Standard 14/61 for both potable water and DWV applications. Information provided by Georgia Gulf Georgia Gulf became

Axiall Corporation in 2013.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Axiall-MD-5009-Rigid-PVC-Molding.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.42 g/cc	1.42 g/cc	ASTM D-792
Linear Mold Shrinkage	0.0020 - 0.0030 cm/cm	0.0020 - 0.0030 in/in	ASTM D-955

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	49.0 MPa	7100 psi	ASTM D-638
Tensile Modulus	2.90 GPa	420 ksi	ASTM D-638
Flexural Strength	89.6 MPa	13000 psi	ASTM D-790
Flexural Modulus	2.96 GPa	430 ksi	ASTM D-790
Izod Impact, Notched	0.374 J/cm	0.700 ft-lb/in	ASTM D-256
	@Thickness 3.17 mm, Temperature -20.0 °C	@Thickness 0.125 in, Temperature -4.00 °F	
	0.587 J/cm	1.10 ft-lb/in	ASTM D-256
	@Thickness 3.17 mm, Temperature 23.0 °C	@Thickness 0.125 in, Temperature 73.4 °F	

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	71.00 °C	159.8 °F	ASTM D-648
Oxygen Index	38 %	38 %	ASTM D-2863

Descriptive Properties	Value	Comments
Cell Classification, ASTM D-1784	12454	NSF std. 14
Flow Ratio (Distance/Wall Thickness, 390-400°F)	175	Georgia Gulf Test

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China