

BASF Lucalen® A 3110 M Ethylene/Acrylate Copolymer

Category : Polymer , Thermoplastic , Ethylene Acrylic Acid

Material Notes:

Economical composite films together with PE-LD; primers for aluminum/steel composites; coatings for paper board, aluminum and steel (e.g. for pipes used to transport petroleum, gas, etc.)Data was collected by ISO methods and provided by BASF.

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Lucalen-A-3110-M-EthyleneAcrylate-Copolymer.php

Physical Properties	Metric	English	Comments
Density	0.928 g/cc	0.0335 lb/in ³	
Water Absorption	0.050 %	0.050 %	
Moisture Absorption at Equilibrium	0.050 %	0.050 %	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	15.0 MPa	2180 psi	
Tensile Strength, Yield	5.00 MPa	725 psi	
Elongation at Break	>= 50 %	>= 50 %	
Tensile Modulus	0.0740 GPa	10.7 ksi	

Thermal Properties	Metric	English	Comments
Melting Point	99.0 °C	210 °F	

Electrical Properties	Metric	English	Comments
Electrical Resistivity	>= 1.00e+15 ohm-cm	>= 1.00e+15 ohm-cm	
Dielectric Constant	2.3	2.3	
	@Frequency 1e+6 Hz	@Frequency 1e+6 Hz	
Dissipation Factor	0.012	0.012	
	@Frequency 1e+6 Hz	@Frequency 1e+6 Hz	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China