

BASF Lupranate® LP30 Isocyanate

Category : Fluid

Material Notes:

Description: Lupranate® LP30 isocyanate is a solvent-free, modified pure diphenylmethane diisocyanate which is liquid at 30°C. It is designed to replace pure MDI in applications where it is desirable to use a product that can be stored as a liquid. It is used as a major starting material in applications such as prepolymers, elastomers, shoe soles, sealants and adhesives. Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Lupranate-LP30-Isocyanate.php

Physical Properties	Metric	English	Comments
Density	1.22 g/cc	0.0441 lb/in ³	
Viscosity	16 cP	16 cP	
Vapor Pressure	1.33e-8 bar @Temperature 25.0 °C	0.00000998 torr @Temperature 77.0 °F	

Thermal Properties	Metric	English	Comments
Boiling Point	>= 190 °C @Pressure 0.000667 MPa	>= 374 °F @Pressure 0.0967 psi	
Flash Point	200 °C	392 °F	

Descriptive Properties	Value	Comments
Color	Pale Yellow	
Composition	NCO content	0.33

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China