

BASF Lupranate® LP30D Isocyanate

Category : Fluid

Material Notes:

Description: Lupranate® LP30D isocyanate is a solvent-free, modified pure diphenylmethane diisocyanate which is liquid at 30°C. It is designed to replace pure MDI in applications where it is desirable to use a product that can be stored as a liquid. It is used as a major starting material in applications such as prepolymers, elastomers, shoe soles, sealants and adhesives. The "D" stands for the drum packaging. Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Lupranate-LP30D-Isocyanate.php

Physical Properties	Metric	English	Comments
Density	1.22 g/cc	0.0441 lb/in ³	
Viscosity	16 cP	16 cP	
Vapor Pressure	1.33e-8 bar @Temperature 25.0 °C	0.00000998 torr @Temperature 77.0 °F	

Thermal Properties	Metric	English	Comments
Boiling Point	>= 190 °C @Pressure 0.000667 MPa	>= 374 °F @Pressure 0.0967 psi	
Flash Point	200 °C	392 °F	

Descriptive Properties	Value	Comments
Color	Pale Yellow	
Composition	NCO content	0.33

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China