

BASF Luwax® OA 5 Pastilles/Powder

Category : Polymer , Thermoplastic , Polyethylene (PE)

Material Notes:

Description: Oxidized polyethylene wax with high hardness and a low acid number. Important applications include emulsion for coating citrus fruit, paper, cellophane, textiles and flooring. Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Luwax-OA-5-PastillesPowder.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	350 - 470	350 - 470	[mm ² /s], Melt; DGF M-III 8
	@Temperature 120 °C	@Temperature 248 °F	

Mechanical Properties	Metric	English	Comments
Ball Indentation Hardness	450 MPa	65300 psi	DGF M-III 9a

Chemical Properties	Metric	English	Comments
Total Acid Number	15 - 19	15 - 19	[mg KOH/g]; DGF M-IV 2

Descriptive Properties	Value	Comments
Color	Off-White	
Congealing Point	98°C	DGF M-III 3

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China