

## BASF Neoplen® 1710 60 mm Expanded Polyethylene

Category : Polymer , Thermoplastic , Polyethylene (PE)

**Material Notes:**

Uses: Foam plates for the production of packaging, sporting goods and technical components. Information provided by BASF

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_BASF-Neoplen-1710-60-mm-Expanded-Polyethylene.php](http://www.lookpolymers.com/polymer_BASF-Neoplen-1710-60-mm-Expanded-Polyethylene.php)

Physical Properties	Metric	English	Comments
Density	0.0100 - 0.100 g/cc @Pressure 0.101 MPa, Temperature 20.0 °C	0.000361 - 0.00361 lb/in <sup>3</sup> @Pressure 14.7 psi, Temperature 68.0 °F	

Thermal Properties	Metric	English	Comments
Decomposition Temperature	>= 140 °C	>= 284 °F	
Flash Point	>= 200 °C	>= 392 °F	ASTM D1929

Processing Properties	Metric	English	Comments
Melt Temperature	100 - 140 °C	212 - 284 °F	

Descriptive Properties	Value	Comments
Commercial Status	Europe	
Ignition Temperature	>360°C	ASTM D1929

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China