

BASF Neopor® 2200 Expandable Polystyrene

Category : Polymer , Thermoplastic , Polystyrene (PS) , Expanded Polystyrene (EPS)

Material Notes:

Description: Expandable polystyrene (EPS) containing uniformly distributed flame retardant (blowing agent: pentane).Remarks: For the production of flame-retardant silver-gray foams having a considerably higher thermal-insulation capacity than the usual EPS insulating materials.Applications: For blocks and thick walled shapes.Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Neopor-2200-Expandable-Polystyrene.php

Physical Properties	Metric	English	Comments
Bulk Density	0.600 g/cc	0.0217 lb/in ³	
Density	0.00310 g/cc	0.000112 lb/in ³	Vapor (Heavier than air)
	1.02 - 1.05 g/cc	0.0368 - 0.0379 lb/in ³	
Bead Size	1.40 - 2.50 mm	0.0551 - 0.0984 in	

Thermal Properties	Metric	English	Comments
Softening Point	70.0 °C	158 °F	approx
Decomposition Temperature	>= 220 °C	>= 428 °F	
Flash Point	>= -56.0 °C	>= -68.8 °F	

Processing Properties	Metric	English	Comments
Moisture Content	<= 3.0 %	<= 3.0 %	

Descriptive Properties	Value	Comments
Color	Black	
Commercial Status	Europe	
Ignition Temperature	285°C	DIN 51794
Sieve Analysis	<1.25 mm	max 2%
	>2.5 mm	max 2%
	1.25 - 2.5 mm	max 96%

Contact Songhan Plastic Technology Co.,Ltd.Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China