

BASF Pluracol® 1158 Specialty Polyol

Category : Fluid

Material Notes:

Description: Pluracol® 1158 polyol is a polyol which can be used in a wide variety of applications. It can be employed as a cross-linking agent for rigid foam as well as coatings and elastomers. When combined with GP series polyols, high heat distortion resistant microcellular products can be produced. Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Pluracol-1158-Specialty-Polyol.php

Physical Properties	Metric	English	Comments
Density	1.10 g/cc	0.0397 lb/in ³	
	@Temperature 43.3 °C	@Temperature 110 °F	
	1.11 g/cc	0.0401 lb/in ³	
	@Temperature 32.2 °C	@Temperature 90.0 °F	
	1.12 g/cc	0.0405 lb/in ³	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Viscosity	600 cP	600 cP	
	@Temperature 43.3 °C	@Temperature 110 °F	
	1300 cP	1300 cP	
	@Temperature 32.2 °C	@Temperature 90.0 °F	
	3400 cP	3400 cP	
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.050 %	<= 0.050 %	STI 3062

Descriptive Properties	Value	Comments
Color	Clear Liquid	
Hydroxyl Number	920 mg KOH.g	STI 3007/3162

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China