

BASF Pluracol® 858 Specialty Polyol

Category : Fluid

Material Notes:

Description: Pluracol® 858 polyol is a modifying polyol which can be used in a wide variety of applications. It can be employed as a cross-linking agent for rigid foam as well as coatings and elastomers. When combined with GP series polyols, high heat distortion resistant microcellular products can be produced. Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Pluracol-858-Specialty-Polyol.php

Physical Properties	Metric	English	Comments
Density	0.986 g/cc	0.0356 lb/in ³	
	@Temperature 43.4 °C	@Temperature 110 °F	
	0.996 g/cc	0.0360 lb/in ³	
	@Temperature 32.2 °C	@Temperature 90.0 °F	
	1.00 g/cc	0.0361 lb/in ³	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Viscosity	285 cP	285 cP	
	@Temperature 43.4 °C	@Temperature 110 °F	
	700 cP	700 cP	
	@Temperature 32.2 °C	@Temperature 90.0 °F	
	1360 cP	1360 cP	
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.050 %	<= 0.050 %	STI 3062

Descriptive Properties	Value	Comments
Color	Clear Liquid	
Hydroxyl Number	935 mg KOH/g	STI 3007/3162

Contact Songhan Plastic Technology Co.,Ltd.Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China