

BASF Pluracol® 922 Rigid Polyol

Category : Fluid

Material Notes:

Description: Pluracol® 922 polyol is an aromatic initiator-based polyol for rigid foams developed for use in spray formulations, or in polyol blends that can utilize its inherent fast reactivity. Pluracol 922 has excellent compatibility with common foam ingredients such as blowing agents most type of polyols, polymeric MDI, and crude TDI. Foams made with Pluracol 922 are characterized by fine cell structure, low K factor, and good dimensional stability. Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Pluracol-922-Rigid-Polyol.php

Physical Properties	Metric	English	Comments
Density	1.05 g/cc	0.0379 lb/in ³	
	@Temperature 60.0 °C	@Temperature 140 °F	
	1.07 g/cc	0.0387 lb/in ³	
	@Temperature 40.0 °C	@Temperature 104 °F	
	1.08 g/cc	0.0390 lb/in ³	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Viscosity	400 cP	400 cP	
	@Temperature 60.0 °C	@Temperature 140 °F	
	1400 cP	1400 cP	
	@Temperature 40.0 °C	@Temperature 104 °F	
	17000 cP	17000 cP	
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.050 %	<= 0.050 %	STI 3062

Descriptive Properties	Value	Comments
Color	Brown Liquid	
Hydroxyl Number	485 - 515 mg KOH/g	STI 3007/3162

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China