

BASF Ultramid® 1503-2 BK ND3007 33% Glass Filled PA66 (Conditioned)

Category : Polymer , Thermoplastic , Nylon , Nylon 66 , Nylon 66, 30% Glass Fiber Filled

Material Notes:

Ultramid 1503-2 BK ND3007 is a 33% glass reinforced, heat stabilized, pigmented black injection molding PA6/6.

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Ultramid-1503-2-BK-ND3007-33-Glass-Filled-PA66-Conditioned.php

Physical Properties	Metric	English	Comments
Density	1.40 g/cc	0.0506 lb/in ³	dry; ISO 1183
Water Absorption	5.7 %	5.7 %	beginning dry; ISO 62
Moisture Absorption at Equilibrium	1.7 %	1.7 %	beginning dry (23°C/50% R.H.); ISO 62
Linear Mold Shrinkage	0.0030 cm/cm	0.0030 in/in	ASTM Data; MD

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	144 MPa	20900 psi	5mm/min; ISO 527

Thermal Properties	Metric	English	Comments
Melting Point	257 °C	495 °F	10 K/min
	257 °C	495 °F	ASTM Test

Descriptive Properties	Value	Comments
Color	Black	
Commercial Status	Active America	
Impact Modified	No	
Primary Processing Technique	Injection Molding	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China