

## BASF Ultramid® B50 01 PA6

Category : Polymer , Thermoplastic , Nylon , Nylon 6 , Nylon 6 , Unreinforced

### Material Notes:

Ultramid B50 01 is a high-viscosity, general-purpose extrusion PA6 grade. It conforms to FDA requirements including, 21 CFR 177.1500,EU Directive 2002/72/EC, the German BfR recommendation "X Polyamide", 1.6.1998 or legislations for other countries will be provided on request.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_BASF-Ultramid-B50-01-PA6.php](http://www.lookpolymers.com/polymer_BASF-Ultramid-B50-01-PA6.php)

Physical Properties	Metric	English	Comments
Relative Viscosity	5.0 cP	5.0 cP	ISO Test; 96 % SAV
Linear Mold Shrinkage	0.0090 cm/cm	0.0090 in/in	ASTM Data; MD

Thermal Properties	Metric	English	Comments
Melting Point	220 °C	428 °F	ASTM Test

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China