

BIW ASTM Class 2D5 Silicone Foam

Category : Polymer , Thermoset , Silicone , Silicone Foam

Material Notes:

Products are a closed cell foam and there fore good for use in damp or liquid applications. A variety of physical properties and foam qualities are available by adjusting the processing parameters. Information provided by BIW Isolierstoffe GmbH.

Order this product through the following link:

http://www.lookpolymers.com/polymer_BIW-ASTM-Class-2D5-Silicone-Foam.php

Physical Properties	Metric	English	Comments
Density	>= 0.400 g/cc	>= 0.0145 lb/in ³	DIN 53479 A

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	>= 15	>= 15	DIN 53505
Compressive Yield Strength	0.120 - 0.170 MPa	17.4 - 24.7 psi	25% Compression
Compression Set	<= 60 % @Temperature 100 °C, Time 79200 sec	<= 60 % @Temperature 212 °F, Time 22.0 hour	50% Compression

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	180 °C	356 °F	Standard Quality, All Colors
	280 °C	536 °F	Highly Temperature Resistant Quality, Opaque, Grey, Blue
Minimum Service Temperature, Air	-60.0 °C	-76.0 °F	Standard Quality, All Colors
Flammability, UL94	V-0	V-0	Self-Extinguishing Quality, Brown

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China