

## BNZ Materials 460 Insulating Cement

Category : Ceramic , Oxide

### Material Notes:

460 Insulating Cement is a 1600°F product, provided in higher density than 508 Insulating Cement. 460 Cement can be applied in heavy layers. It is frequently used as the principal covering on pipe sizes smaller than 4", then covered with a finish of 375 Finishing Cement.

Typical Applications: Insulating and Sealing: For kiln and furnace refractory crowns and domes, and flat suspended arches. Insulation of small steel pipe fittings

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_BNZ-Materials-460-Insulating-Cement.php](http://www.lookpolymers.com/polymer_BNZ-Materials-460-Insulating-Cement.php)

| Thermal Properties               | Metric | English | Comments |
|----------------------------------|--------|---------|----------|
| Maximum Service Temperature, Air | 871 °C | 1600 °F |          |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| Color                  | Grey  |          |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China