

Bapolan® 6409 Polystyrene, Injection Grade

Category : Polymer , Thermoplastic , Polystyrene (PS)

Material Notes:

Bapolan PS6409 is designed for injection molding applications requiring superior impact and gloss. It complies with US FDA21 CFR177.1640 and 94HB UL rating. Application: General purpose. Bapolene® and Bapolan® are registered trademarks of Bamberger Polymers, Inc. Information provided by Bamberger Polymers. All data is based on molded plaques.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Bapolan-6409-Polystyrene-Injection-Grade.php

Physical Properties	Metric	English	Comments
Melt Flow	9.0 g/10 min	9.0 g/10 min	200°C/5,000g; ASTM D-1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	20.7 MPa	3000 psi	ASTM D-638
Elongation at Yield	52 %	52 %	ASTM D-638
Flexural Modulus, 1% Secant	2068 MPa	299900 psi	ASTM D-790A
Izod Impact, Notched	1.34 J/cm	2.51 ft-lb/in	@23°C; ASTM D-256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	87.0 °C	189 °F	ASTM D-648

Descriptive Properties	Value	Comments
Process	Extrusion	
	Injection Molding	
Region	Europe/Turkey	Bamberger Polymers Distribution
	International	Bamberger Polymers Distribution
	Mexico	Bamberger Polymers Distribution
	US & Canada	Bamberger Polymers Distribution

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China