

Bapolan® PS6078-G Polystyrene Compound

Category : Polymer , Thermoplastic , Polystyrene (PS) , Polystyrene, Impact Modified

Material Notes:

Bapolan 6078-G is a colored, high impact polystyrene. Applications: General purpose. Bapolene® and Bapolan® are registered trademarks of Bamberger Polymers, Inc. Information provided by Bamberger Polymers. All data is based on molded plaques.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Bapolan-PS6078-G-Polystyrene-Compound.php

Physical Properties	Metric	English	Comments
Melt Flow	8.0 g/10 min	8.0 g/10 min	200°C/5,000g; ASTM D-1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	20.7 MPa	3000 psi	ASTM D-638
Flexural Modulus, 1% Secant	2068 MPa	299900 psi	ASTM D-790A
Izod Impact, Notched	0.850 J/cm	1.59 ft-lb/in	ASTM D-256

Descriptive Properties	Value	Comments
Process	Injection Molding	
Region	Europe/Turkey	
	International	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China