

Bapolene® 1057 Polyethylene, Extrusion Coating

Category: Polymer, Thermoplastic, Polyethylene (PE), LDPE

Material Notes:

Bapolene 1057 is low high density polyethylene for high speed extrusion coating applications that require superior adhesion and low neck-in. It complies with US FDA 21CFR177.1520.Applications: Pouches, paper coating, and flexible packaging.Bapolene® and Bapolan® are registered trademarks of Bamberger Polymers, Inc. Information provided by Bamberger Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer_Bapolene-1057-Polyethylene-Extrusion-Coating.php

Physical Properties	Metric	English	Comments
Density	0.920 g/cc	0.0332 lb/in³	ASTM D-792
Melt Flow	7.0 g/10 min	7.0 g/10 min	ASTM D-1238

Mechanical Properties	Metric	English	Comments	
Elmendorf Tear Strength MD	10 g	10 g		
Heat Seal Strength	1270 g/25 mm	2.80 lb/in	ASTM D-517	

Descriptive Properties	Value	Comments
Process	Extrusion	
Region	Europe/Turkey	
	International	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China