

Borealis Borflow™ HL504FB Polypropylene Homopolymer

Category: Polymer, Thermoplastic, Polypropylene (PP), Polypropylene, Molded

Material Notes:

Borflow HL504FB is a polypropylene homopolymer grade intended for fiber applications characterized by narrow molecular weight distribution, controlled rheology, easy processability, optimal product consistency, and very high flow.Borflow HL504FB is designed for the production of micro denier fibers at high spinning speeds and typical for meltblown applications.Information provided by the Manufacturer.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Borealis-Borflow-HL504FB-Polypropylene-Homopolymer.php

Physical Properties	Metric	English	Comments
Melt Flow	450 g/10 min	450 g/10 min	ISO 1133
	@Load 2.16 kg, Temperature 230 °C	@Load 4.76 lb, Temperature 446 °F	

Thermal Properties	Metric	English	Comments
Melting Point	161 - 165 °C	322 - 329 °F	ISO 3146

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China