

## Borealis Borseal™ TD110BF Terpolymer for BOPP Film

Category : Polymer , Film , Thermoplastic

**Material Notes:**

Borseal TD110BF is a C2/C4 terpolymer film resin. Borseal TD110BF is especially developed for use as sealing layers in coextruded BOPP film (manufactured on Stenter frame and double bubble film processes). Information provided by the Manufacturer.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Borealis-Borseal-TD110BF-Terpolymer-for-BOPP-Film.php](http://www.lookpolymers.com/polymer_Borealis-Borseal-TD110BF-Terpolymer-for-BOPP-Film.php)

Physical Properties	Metric	English	Comments
Melt Flow	6.5 g/10 min @Load 2.16 kg, Temperature 230 °C	6.5 g/10 min @Load 4.76 lb, Temperature 446 °F	ISO 1133

Mechanical Properties	Metric	English	Comments
Flexural Modulus	0.700 GPa	102 ksi	ISO 178
Heat Seal Strength Initiation Temperature	103 °C	217 °F	3 N; Borealis Test

Thermal Properties	Metric	English	Comments
Melting Point	128 - 132 °C	262 - 270 °F	ISO 3146
Vicat Softening Point	114 °C	237 °F	10 N; ISO 306

Optical Properties	Metric	English	Comments
Haze	1.8 %	1.8 %	ASTM D1003

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China