

Borealis CA7230 Low Density Polyethylene

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE

Material Notes:

CA7230 is a low-density polyethylene for extrusion coating. CA7230 contains no additives. Applications: Extrusion coating of high volume production of boards and papers. Coating of various plastic films and cellophane, Coating and lamination of aluminum foil, Co-extrusion applications. Information provided by Borealis AG

Order this product through the following link:

http://www.lookpolymers.com/polymer_Borealis-CA7230-Low-Density-Polyethylene.php

Physical Properties	Metric	English	Comments
Density	0.923 g/cc	0.0333 lb/in ³	ISO 1183
Melt Flow	4.5 g/10 min @Load 2.16 kg, Temperature 190 °C	4.5 g/10 min @Load 4.76 lb, Temperature 374 °F	ISO 1133
Neck In	6.80 cm	2.68 in	BTM 14920
Coating Weight	>= 7.00 g/m ²	>= 4.38 lb/ream	BTM 14922

Descriptive Properties	Value	Comments
Coating Speed (m/min)	< 700	BTM 14921

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China