

Borealis CA9150 Low Density Polyethylene

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE

Material Notes:

CA9150 is a low-density polyethylene for extrusion coating. CA9150 contains no additives. Applications: coating and lamination of aluminum foil, coating of various plastic films and cellophane, and extrusion coating of high volume production of boards and papers. Information provided by Borealis AG

Order this product through the following link:

http://www.lookpolymers.com/polymer_Borealis-CA9150-Low-Density-Polyethylene.php

Physical Properties	Metric	English	Comments
Density	0.915 g/cc	0.0331 lb/in ³	ISO 1183
Melt Flow	15 g/10 min @Load 2.16 kg, Temperature 190 °C	15 g/10 min @Load 4.76 lb, Temperature 374 °F	ISO 1133
Neck In	6.30 cm	2.48 in	BTM 14920
Coating Weight	>= 5.00 g/m ²	>= 3.13 lb/ream	BTM 14922

Descriptive Properties	Value	Comments
Coating Speed (m/min)	< 650	BTM 14921

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China